

产品选型表

XN700型	XN700直连式单晶硅压力变送器								
	量程范围	-100KPa~0~0.1~60MPa~100M							
		输出信号							
		S1	4~20mA DC HART协议						
		S2	其他（可联系客服定制）						
			过程连接						
			C1	1/2NPT内螺纹					
			C2	1/2NPT外螺纹					
			C3	M20*1.5外螺纹					
			C4	其他（可联系客服定制）					
				接液部分材质					
				G1	316L				
				G2	其他（可联系客服定制）				
					外壳材质				
				1	铸铝合金				
				2	不锈钢				
					电气连接				
				V1	1/2NPT内螺纹				
				V2	M20*1.5内螺纹				
					安装支架				
					N	无			
					B1	不锈钢支架			
					B2	镀锌碳钢支架			
						显示表头			
					M5	LED数字显示表头			
XN700型	0~1MPa	S1	C3	G1	V1	M5	B2	M5	选型举例：XN700（0~1MPa）S1C3G11V1B2M5

量程代码

代码	量程	代码	量程	代码	量程
01	0~10KPa	18	0~50KPa	35	0~50KPa
02	-100KPa~0	19	100~100K	36	0~0.6MPa
03	0~1MPa	20	0~1.6MPa	37	0~2.5MPa
04	0~6MPa	21	0~10MPa	38	0~20MPa
05	0~30MPa	22	0~40MPa	39	0~60MPa
06	0~80MPa	23	0~100MPa	40	其他量程定制