

# 产品选型表

XN900型	XN900单晶硅压力/差压变送器									
变送器类型										
Y	压力变送器									
C	差压变送器									
测量范围	-500KPa~0~10KPa~100KPa~500KPa									
输出信号										
S1	4~20mA DC HART协议									
过程连接										
A	1/4NPT内螺纹过程接头									
B	法兰安装, 见附表									
接液部分材质										
C1	316L									
C2	哈氏合金C-276									
C3	钽									
C4	参考法兰参数表									
外壳材质										
1	铸铝合金									
2	不锈钢									
电气连接										
V1	1/2NPT内螺纹									
V2	M20*1.5内螺纹									
安装支架										
N	无									
B1	不锈钢支架									
B2	镀锌碳钢支架									
显示表头										
M5	LED数字显示表头									
XN900型	0~100KPa	S1	A	C1	1	V1	B2	M5	选型举例: XN900 ( 0~100KPa ) S1AC11V1B2M5	

量程代码			
代码	量程	代码	量程
01	0~1KPa	18	0~100KPa
02	-500KPa~0	19	0~200KPa
03	0~10KPa	20	0~250KPa
04	0~30KPa	21	0~350KPa
05	0~50KPa	22	0~500KPa
06	0~80KPa	23	其他量程定制

